


AF80

Android MiniPOS



Powered by
Android 7.x



PCI PTS
6.x Certified



5-inch Color
Touchscreen









Omni-channel
Payment




















4G, 3G, GPRS
Wi-Fi, Bluetooth

HIGHLIGHTS

-  New paperless mobile terminal, compact & light
-  Hyper stable performance based on Android OS
-  Snappy capture of 1D & 2D barcode, a helper of logistics, warehousing etc.
-  Full peripheral ports, accepting various payment transactions
-  Support numerous value-added applications
-  With Payment Management System, making payment management remotely and securely

SPECIFICATIONS

	Operating System	Android 7.x		
	Processor	ARM Quad-core Cortex processor 32-bit secure processor		
	Memory	8GB Flash + 1GB SDRAM 16GB Flash + 2GB SDRAM (Optional) Micro SD (TF) card up to 32G		
	Display	5-inch 1280 x 720 pixels IPS color display Capacitive touchscreen		
	Physical Key	1 x ON / OFF key / 1 x Volume key / 1 x Scan key		
	Card Readers	Magnetic Card Reader Track1 / 2 / 3, Bi-directional ISO 7812-2	Smart Card Reader ISO7816, EMV Level 1 & Level 2	Contactless Card Reader Mifare classic / Mifare Ultralight / Mifare DESFire ISO 14443 A & B Visa payWave MasterCard Contactless
	Communications	Wi-Fi (supports hotspot)	4G / 3G / GPRS	Bluetooth
	Satellite Positioning	GPS / GLONASS / BEIDOU		
	Peripheral Ports	2 x SIM	1 x SAM	1 x Type-c 1 x SD
	Camera	Front: 0.3 Megapixel Rear: 5 Megapixel with Flash & AF Hard decoding module scanning head (Optional)		
	Audio	Buzzer / Speaker / Microphone		
	Indicators	4 x Contactless transaction lights		
	Security	Built-in PINPad (virtual keyboard) ANSI X9.8 / ISO95 64, ANSI X9.9 / ISO8731 Master key / Session key Fixed and DUKPT PIN secure resolutions DES / 3DES / RSA / SHA-256 / AES algorithms		
	Power	Input: 110 - 240V AC, 50Hz / 60Hz Output: 5.0V DC, 1.0A Type-C port, anti-lightning, anti-static-electricity		
	Battery	3.7V / 2200mAh rechargeable Li-ion battery		
	Environmental	0°C ~ 50°C operating temperature -20°C ~ 70°C storage temperature 10% ~ 90% relative humidity, non-condensing		
	Certifications	PCI PTS 6.x EMV L1 & L2 EMV Contactless L1 MasterCard Contactless	Visa payWave JCB Contactless RuPay Contactless American Express	Discover D-PAS TQM UPI CE & RoHS

Android MiniPOS